

WARNING: IMPROPER SELECTION OR USE OF LPH QUICK COUPLINGS CAN RESULT IN PERSONAL INJURY, PROPERTY DAMAGE AND EVEN DEATH.

THUS THE FOLLOWING IS ESSENTIAL AND UTMOST IMPORTANT:

- 1» PLEASE DESIGN A SYSTEM OR DEVICE USED FOR SECURITY PROTECTION (PRESSURE RELIEF DEVICE, EXCESS OIL PRESSURE DEVICE, ETC). EVEN IF THERE IS A PROBLEM DUE TO IMPROPER OPERATION OF A PART, IT WILL NOT RESULT IN SERIOUS PERSONAL AND PROPERTY DAMAGE.
- 2) DURING INSTALLATION, IT IS EASIER TO BE BROKEN IF EXCESSIVE TIGHTENING.PLEASE USE PROPER TORQUE.
- 3 DO NOT PRESSURIZE COUPLINGS BEYOND THEIR RATED OPERATING PRESSURE.
- ENSURE COMPATIBILITY OF COMPONENTS AND SEALS WITH THE CLEAN FLUID BEING CONVEYED.

www.nbhydraulic.com

www.nbhydraulic.com

- 5» AVOID EXTERMAL FORCES ACTING ON THE COUPLINGS SUCH AS TENSILE, SIDE LOADS, VIBRATION OR HAMMERING.
- DO NOT PRESSURIZE ONLY FOR FEMALE OR MALE.

www.nbhydraulic.com

.nbhydraulic.com

uraulic.com

N.nbhydraulic.com

www.nbhydraulic.com

www.nbhydraulic.com

www.nbhydraulic.com

www.nbhydraulic.com

DO NOT DISCONNECT COUPLINGS UNDER PRESSURE UNLESS UTILIZING COUPLINGS DESIGNED FOR THAT PURPOSE. www.nbhydra

www.nbhydraulic.com

www.nbhydraulic.com

www.nbhydraulic.com

www.nbhydraulic.com

www.nbhydraulic.com

8) IF RESIDUAL PRESSURE, PLEASE AVOID HAMMERING THE VALVES.

IN ALL CASED OF DOUBT, PLEASE DO NOT HESITATE TO CONTACT US ANS WE WILL SUPPLY YOU WITH DETAILED INSTRUCTIONS CONCERNING MAINTENANCE&INSTALLATION.

www.nbhydraulic.com

www.nbhydraulic.com